

# HAX815X

## TP Rcpp

**Jean-Michel Marin**

Professeur Université de Montpellier  
Faculté des Sciences

Février 2023

For each of the following functions, read the code and figure out what the corresponding base R function is. You might not understand every part of the code yet, but you should be able to figure out the basics of what the function does.

```
double f1(NumericVector x) {
  int n = x.size();
  double y = 0;

  for(int i = 0; i < n; ++i) {
    y += x[i] / n;
  }
  return y;
}
```

```
NumericVector f2(NumericVector x) {
  int n = x.size();
  NumericVector out(n);

  out[0] = x[0];
  for(int i = 1; i < n; ++i) {
    out[i] = out[i - 1] + x[i];
  }
  return out;
}
```

```
bool f3(LogicalVector x) {
  int n = x.size();

  for(int i = 0; i < n; ++i) {
    if (x[i]) return true;
  }
  return false;
}
```

```

int f4(Function pred, List x) {
    int n = x.size();

    for(int i = 0; i < n; ++i) {
        LogicalVector res = pred(x[i]);
        if (res[0]) return i + 1;
    }
    return 0;
}

NumericVector f5(NumericVector x, NumericVector y) {
    int n = std::max(x.size(), y.size());
    NumericVector x1 = rep_len(x, n);
    NumericVector y1 = rep_len(y, n);

    NumericVector out(n);

    for (int i = 0; i < n; ++i) {
        out[i] = std::min(x1[i], y1[i]);
    }

    return out;
}

```

To practice your function writing skills, convert the following functions into C++.

- cumprod(), cummin()
- diff(lag=1)
- range()
- var()